



紅外線溫度計

Specifications	ST685	ST688	ST689	ST688 Plus
Distance/Spot Ratio	30:1	50:1	50:1	50:1
Temperature Range	-50~ 1000°C(-58~ 1832°F)			-50~ 1500°C(-58~ 2732°F)
Accuracy (Assumes Operation Ambient Temperature of 25°C/77°F)	±3°C(±5°F) -50~ -20°C(-58~ -4°F) ±2°C(±3°F) -20~ 100°C(-4~ 212°F) ±2% 100~1000°C(212~1832°F)			±3°C(±5°F) -50~ -20°C(-58~ -4°F) ±2°C(±3°F) -20~ 100°C(-4~ 212°F) ±2% 100~1500°C(212~2732°F)
Thermopile	8~14 μm			
Repeatability	±1°C(±2°F)			
Resolution	0.1°C(0.1°F)			
Response Time	500ms			
Operation Temp	0~50°C(32~122°F),10~90%RH			
Auto Power Off	Automatically after approx. 6sec			
Emissivity	Adjustable 0.1~1.0			
°C/°F Switchable	YES	YES	YES	YES
Backlight	YES	YES	YES	YES
Laser Sight Switchable	YES	YES	YES	YES
Max/Min/Avg./ΔT	YES	YES	YES	YES
Auto-measuring	YES	YES	YES	YES
10 point memory	YES	YES	YES	YES
Audio Alarm	YES	YES	YES	YES
Dual Display	YES	YES	YES	YES
Tripod Mount	YES	YES	YES	YES
USB Data Output	NO	NO	YES	NO
Thermocouple K Type	NO	NO	YES	NO
Dimensions	200×127×47 mm			